

JOYALL

RIDE WITH THE BEST

JOYALL



A812 A808

Heavy load on mixed road.

SIZE	Ply	Load Index/Speed	Depth(mm)
315/80R22.5	20	157/154K	23.0
12.00R20	20	156/153K	20.0
13R22.5 A808	20	156/153K	20.0



A815

Heavy load on mixed road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12.00R20	20	156/153J	21.0
13R22.5	20	156/153K	21.3



B958

Heavy load on mixed road.

SIZE	Ply	Load Index/Speed	Depth(mm)
10.00R20	18	149/146J	21.5
11.00R20	18	152/149J	21.0



A928

On mixed road at mid speed.

SIZE	Ply	Load Index/Speed	Depth(mm)
295/80R22.5	20	154/150J	21.0
315/80R22.5			
325/95R24			
12R22.5	18	152/149K	24.0
12.00R20			
12.00R24			



A903

Heavy load on rough road.

SIZE	Ply	Load Index/Speed	Depth(mm)
295/80R22.5	20	154/150D	21.0



A906

Heavy load on rough road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12R22.5	18	152/149F	24.0
13R22.5	20	156/153D	24.0
11.00R20	18	152/149D	24.0
12.00R20	20	156/153D	24.0



A916

Overload mining on bad gravel road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12.00R20	20	156/153D	22.5



A66+ A990

Heavy load on mixed road.

SIZE	Ply	Load Index/Speed	Depth(mm)
9.00R20	16	144/142D	24.5
10.00R20	18	149/146D	24.5
11.00R20	16	150/147D	25.0
12.00R20 A990	18	154/151D	24.0



A907 A915

Overload mining on bad gravel road.

SIZE	Ply	Load Index/Speed	Depth(mm)
11.00R20	18	152/149D	28.0
12.00R20	20	156/153D	26.0 /23.0



A908

Heavy load mining on unpaved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12R22.5	18	152/149F	26
11.00R20	18	152/149D	26
12.00R20	20	156/153D	25

RIDE WITH THE BEST

JOYALL



A913

Overload mining on bad gravel road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12.00R20	20	156/153B	32.0

NOTES

RIDE WITH THE BEST



Commercial Vehicle Tyre Products

2024

JOYALL

SIZE	PATTERN
7.00R16LT	A605
7.50R16LT	A605 B875 A515
8.25R16LT	A515 A605
9.00R20	A66+/A990
10.00R20	A608+ A9 A66+/A990 A958 B958
11.00R20	A608+ A9 A66+/A990 A906 A907/A915 A908 A958 A959 B958
12.00R20	A9 A958 A815 A906 A907/A915 A908 A913 A916 A66+/A990 A812/A808 A928
12.00R24	A505 B875 A807 A928
11R22.5	A608+ A875 A503 A878 B875 A501 A508 A9 B878/G201 A805 A876/G102
11R24.5	A876/G102 A878
12R22.5	A608+ A605 A889 B875 A501 A506 A509 A919 B878/G201 A958 A803 A888+ A928 A906 A908
13R22.5	A889 A9 A958 A906 A812/A808 A815
215/75R17.5	A608+
235/75R17.5	A605
275/70R22.5	A501 A503
275/80R22.5	A605
295/60R22.5	A605
295/75R22.5	A875 A876/G102 A878
295/80R22.5	A608+ A8/A606 A876/G102 A503 A705 B878/G201 A928 A903 A702
315/70R22.5	A8/A606 A702
315/80R22.5	A608+ A8/A606 A876/G102 B875 A702 B878/G201 A802 A888+ A812/A808 A928 A919
385/65R22.5	A601 A610 A615
285/75R24.5	A876/G102 A878
325/95R24	A928
385/55R22.5	A610

RIDE WITH
THE BEST

JOYALL



On highway or good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
215/75R17.5	16	135/133L	13.0
295/80R22.5	18	152/149L	16.5
315/80R22.5	20	157/154K	16.0
11R22.5	18	149/146L	16.5
12R22.5	18	152/149L	17.5
10.00R20	18	149/146K	16.5
11.00R20	18	152/149K	16.5



On good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
295/80R22.5	18	152/149M	16.5
315/70R22.5	18	151/148L	16.5
315/80R22.5	20	157/154L	16.5



On highway or good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
7.00R16LT	14	118/114L	12.0
7.50R16LT	16	125/121L	13.0
8.25R16LT	18	132/128L	14.5
235/75R17.5	18	143/141J	13.0
275/80R22.5	18	149/146L	16.5
295/60R22.5	18	150/147L	17.0
12R22.5	18	152/149L	17.0



Standard/ overload on good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
285/75R24.5	16	147/144L	14.5
295/75R22.5	16	146/143L	15.0
295/80R22.5 G102	18	152/149M	15.0
315/80R22.5	20	157/154L	15.0
11R22.5	16	146/143L	15.0
11R24.5	16	149/146L	15.0



On highway or good paved road

	Ply	Load Index/Speed	Depth(mm)
295/75R22.5	16	146/143L	11.0
11R22.5	16	146/143L	11.0



Overload on paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
385/65R22.5	24	164J	16.5



Overload on paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
385/65R22.5	24	164J	16.0
385/55R22.5	20	160K	15.0



Overload on paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
385/65R22.5	24	164J	15.5



Urban and intercity short distance.

SIZE	Ply	Load Index/Speed	Depth(mm)
275/70R22.5	18	150/145J	22.0
295/80R22.5	18	152/149K	21.0
11R22.5	16	148/145J	22.0



Overload on highway or good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12R22.5	18	152/149L	17.5



Overload on paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12.00R24	20	160/157K	16.0



Overload on highway or good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12R22.5	18	152/149L	16.5
13R22.5	20	156/153K	16.5



Overload on good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12R22.5	18	152/149L	18.0



Overload on paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12R22.5	18	152/149L	16.5
315/80R22.5			



Overload on highway or good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
7.50R16LT	16	125/121L	12.5
315/80R22.5	20	157/154L	16.0
11R22.5	16	148/145L	15.0
12R22.5	18	152/149L	15.0
12.00R24	20	160/157K	17.0



RIDE WITH
THE BEST

JOYALL



Heavy load on paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
7.50R16LT	16	125/121L	14.0
8.25R16LT	18	132/128L	14.5



Heavy load on paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
11R22.5	18	149/146L	16.0
13R22.5	20	156/153K	17.0
10.00R20	18	149/146K	16.0
11.00R20	18	152/149K	16.5
12.00R20	20	156/153K	17.0



On paved road at mid-low speed.

SIZE	Ply	Load Index/Speed	Depth(mm)
11.00R20	18	152/149K	15.0



Urban and intercity short distance.

SIZE	Ply	Load Index/Speed	Depth(mm)
275/70R22.5	16	148/145J	28.0
11R22.5	16	148/145J	27.5
12R22.5	18	152/149L	27.0



Urban and intercity short distance.

SIZE	Ply	Load Index/Speed	Depth(mm)
11R22.5	16	148/145J	22.0



Overload on highway or good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
285/75R24.5	16	147/144L	21.5
295/75R22.5	16	146/143L	22.0
11R24.5	16	149/146L	21.5
11R22.5	16	146/143L	22.0



Overload on highway or good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
315/70R22.5	18	151/148L	24.5
315/80R22.5	20	157/154K	23.0
295/80R22.5			



On paved road at high speed.

SIZE	Ply	Load Index/Speed	Depth(mm)
315/80R22.5	20	157/154K	24.0
12R22.5	18	152/149L	23.0



Overload on highway or good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
295/80R22.5	18	152/149L	18.5



Overload on highway or good paved road.

SIZE	Ply	Load Index/Speed	Depth(mm)
295/80R22.5	18	152/149M	22.0
315/80R22.5	20	157/154L	22.0
11R22.5	16	146/143L	22.0
12R22.5	18	152/149L	22.0



RIDE WITH
THE BEST

JOYALL



On toughest road conditions at extra-heavy load.

SIZE	Ply	Load Index/Speed	Depth(mm)
11R22.5	16	148/145K	23.0



On mixed road conditions at heavy load.

SIZE	Ply	Load Index/Speed	Depth(mm)
12.00R24	20	160/157K	24.5



Heavy load on mixed road.

SIZE	Ply	Load Index/Speed	Depth(mm)
12R22.5	18	152/149K	19.0
13R22.5	22	158/156G	19.0
10.00R20	18	149/146K	18.0
11.00R20	18	152/149K	19.0
12.00R20	20	156/153K	19.0



On mixed road conditions at mid-low speed.

SIZE	Ply	Load Index/Speed	Depth(mm)
12R22.5	18	152/149K	23.0



Heavy load on mixed road.

SIZE	Ply	Load Index/Speed	Depth(mm)
315/80R22.5	20	157/154D	24.5

